

BDTM SERIES

DIGITORQON™




Features

- ✓ Tightening torque measurement works in both clockwise and counter-clockwise direction
- ✓ Digital read – out & SD Storage of Tightening Torque
- ✓ High repeated accuracy: $\pm 3\%$
- ✓ Calibration Certificate Included



Specifications



Model	Reading Range	Reading Accuracy	Battery	Battery Life	Operating Temperature	Adaptable Model	Dimensions				Weight	
							D	L	D	L	kg	lb
BDTM5EN BDTM5EF	100 - 550 (BDTM5EN) N.m 80- 400(BDTM5EF) lbf.ft	$\pm 3\%$	AAA Alkaline X 4 or Nickel Metal Hydride Rechargeable Battery	Approx 10,000 readings	0-40°C/ 32-104°F humidity below 80% (no condensation allowed)	GSR551E/ GSR52E GNR31E-CE/ GNR32E-CE GNR31E-UC/ GNR51E-CE GNR52E-CE/ GNR51E-UC	95	117	3.7	4.6	1.7	3.7
BDTM8EN BDTM8EF	250-850 (BDTM8EN) N.m 190-620 (BDTM8EF) lbf.ft					GSR71E/ GSR72E GNR81E-CE/ GNR82E-CE GNR81E-UC	95	117	3.7	4.6	1.7	3.7
BDTM12EN BDTM12EF	550-1250 (BDTM12EN) N.m 410- 920 (BDTM12EF) lbf.ft					GSR121E/GSR122E GNR121E-CE/ GNR122E-CE GNR121E-UC	106	124	4.2	4.9	2.4	5.3
BDTM21EN BDTM21EF	840-2160 (BDTM21EN) N.m 620-1590 (BDTM21EF) lbf.ft					GSR211E/ GSR212E GNR211E-CE/ GNR212E-CE GNR211E-UC	115	129	4.5	5.1	3	6.6

Standard Accessories

Hex Key Wrench (4mm)	1	Calibration Certificate w/ Traceability Diagram	1
(-) Screw Driver	1	Metal Case	1
AAA Alkaline Battery	4	MicroSD Memory Card Set	1
Instruction Manual	1		



SCAN ME



Tel: +65 6271 0800
 Fax: +65 6273 3121
enquiries@petracarbon.com
www.petracarbon.com



bizSAFE₃