

# SEAL-TITE

## Leak Sealing Solution



### Designed for Multiple Industries



Mediums	Compound Types (PC)					
	71	71B	76	76B	77	79
Urea (165 Bar/185 C)	Yes	Yes				
Nitric Acid	Yes	Yes			Yes	Yes
Hexane	Yes		Yes	Yes		
Oxydye Ethylene						Yes
Sulfuric Acid						Yes
Crude Oil	Yes	Yes				
Furfural	Yes	Yes				
Kerozen	Yes	Yes				
Hydrogen	Yes	Yes			Yes	
H2 Sulfur	Yes	Yes				
Ammonia	Yes	Yes				
Arsenic	Yes	Yes				
Sulfulan	Yes	Yes				
Alkylate	Yes	Yes				
Chloride	Yes	Yes				

## Injection Equipment

Our long experience has enabled us to develop the most reliable and most efficient injection tools. Very fast and safe injection procedure.

The most basic and most economical maintenance requirements.

## Sealing Compound

A wide range of sealing compounds, specially manufactured to meet all types of leaks: steam, hydrocarbons, acids and water.

The very best combination of sealing ingredients enables fluid, fast injections. Our special packaging guarantees a 24 months storage period.

## Steam, Water, and Air

- PC70** For high temperature (700 °C) and high pressure (240 Bar)
- PC70B** Reinforced for difficult leak
- PC72** Special for small gaps and reinjection
- PC76B** Max temperature (300 °C) and max pressure (70 Bar)

## Hydrocarbon

- PC71** High temperature (700°C) and high pressure (240 Bar)
- PC77** Special for small gaps and reinjection

## Chemical and Acid

- PC79** PTFE based compound

SCAN ME



Tel: +65 6271 0800  
 Fax: +65 6273 3121  
[enquiries@petracarbon.com](mailto:enquiries@petracarbon.com)  
[www.petracarbon.com](http://www.petracarbon.com)

